













■ RADIAL-LEADED

Photo	Series	Hold Current	Rated Voltage	Max Current	Temp. Range	Description
	FRV	0.05A ~ 2.0A	240Vac/dc	1A ~ 20A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Power Supply, Appliance 2. Low Hold Current 3. Radial-Leaded
	FRX	0.05A ~ 3.75A	60Vdc	40A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Low Hold Current 2. Radial-Leaded
	FRX90V	0.1A ~ 3.75A	72 / 90Vdc			
	FRK-M	0.05A ~ 5.0A	60Vdc	40A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Reduced Size 2. Radial-Leaded
	FUSB	0.75A ~ 2.5A	16Vdc ~ 30Vdc	40A	-40°C to 85°C	<ol style="list-style-type: none"> 1. USB Application 2. Low Resistance 3. Fast Trip Time 4. Lower Trip-To-Hold Ratio 5. Radial-Leaded
	FRH	0.08A ~ 0.18A	250V, 600Vdc	3A ~ 10A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Telecom / Data 2. Low Hold Current 3. Radial-Leaded
	FRHV		100V, 250V			

■ **RADIAL-LEADED (Cont'd)**

Photo	Series	Hold Current	Rated Voltage	Max Current	Temp. Range	Description
	FBR	0.1A ~ 0.9A	90Vdc	40A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Cable / Telecom 2. Low Hold Current 3. Radial-Leaded
	FRVL	0.1A ~ 3.75A	120Vac/dc	2A ~ 20A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Power Supply / Appliance 2. Radial-Leaded
	FRT	0.50A ~ 2.50A	36Vdc	40A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Fast Trip Time 2. Lower Trip-To-Hold Ratio 3. Radial-Leaded
	FHT	0.5A ~ 15.0A	16Vdc ~ 30Vdc	40A ~ 100A	-40°C to 125°C	<ol style="list-style-type: none"> 1. Very Low Resistance 2. Very High Hold Current 3. Radial-Leaded
	FRU	0.90A ~ 9.0A	30Vdc	40A	-40°C to 85°C	<ol style="list-style-type: none"> 1. High Hold Current 2. Low Resistance 3. Radial-Leaded
	FRG	2.5A ~ 14.0A	16Vdc	100A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Very High Hold Current 2. Radial-Leaded

■ SURFACE MOUNT

Photo	Series	Hold Current	Rated Voltage	Max Current	Temp. Range	Description
	FSMD0805	0.1A ~ 1.0A	6V ~ 15Vdc	40A ~ 100A	-40°C to 85°C	1. 0805 Size Surface Mount 2. Fast Trip Time 3. Low Resistance
	FSMD1206	0.05A ~ 2.0A	6V ~ 60Vdc	10A ~ 100A	-40°C to 85°C	1. 1206 Size Surface Mount 2. Fast Trip Time 3. Low Resistance
	FSMD1210	0.05A ~ 1.5A	6V ~ 60Vdc	10A ~ 100A	-40°C to 85°C	1. 1210 Size Surface Mount 2. Fast Trip Time 3. Low Resistance
	FSMD1812	0.1A ~ 3.0A	6V ~ 60Vdc	10A ~ 100A	-40°C to 85°C	1. 1812 Size Surface Mount 2. Fast Trip Time 3. Low Resistance
	FSMD2920	0.3A ~ 3.0A	6V ~ 60Vdc	10A ~ 40A	-40°C to 85°C	1. 2920 Size Surface Mount 2. Fast Trip Time 3. Low Resistance

■ **AXIAL LEADED**

Photo	Series	Hold Current	Rated Voltage	Max Current	Temp. Range	Description
	FLT	0.7A ~ 3.4A	24Vdc	100A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Low Profile 2. Rechargeable Battery Packs 3. Computer
	FVT	1.1A ~ 2.4A	16Vdc	100A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Low Profile 2. Rechargeable Battery Packs 3. Computer
	FSR	1.2A ~ 4.2A	15Vdc ~ 30Vdc	100A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Low Profile 2. Rechargeable Battery Packs 3. Computer
	FSL	1.4A ~ 4.5A	6Vdc	100A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Low Profile 2. Rechargeable Battery Packs 3. Computer
	FVL	1.7A ~ 2.3A	12Vdc	100A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Low Profile 2. Rechargeable Battery Packs 3. Computer
	FLR	1.9A ~ 7.3A	15Vdc ~ 20Vdc	100A	-40°C to 85°C	<ol style="list-style-type: none"> 1. Low Profile 2. Rechargeable Battery Packs 3. Computer