

	NO.	PQ29-111E		
	Product Specification and Approval Sheet	Version	1	Page

Surface Mountable PTC Resettable Fuse: Low Rho FSMD0805 Series

1. Summary

- (a) **RoHS Compliant & Halogen Free**
- (b) **Applications: All high-density boards**
- (c) **Product Features: Small surface mountable, Solid state, Faster time to trip than standard SMD devices, Lower resistance than standard SMD devices**
- (d) **Operation Current: 0.75A~3.50A**
- (e) **Maximum Voltage: 6V_{DC}**
- (f) **Temperature Range: -40°C to 85°C**

2. Agency Recognition

UL: File No. E211981
C-UL: File No. E211981
TÜV: File No. R50090556

3. Electrical Characteristics (23°C)

Part Number	Hold Current	Trip Current	Rated Voltage	Max. Current	Typical Power	Max. Time to Trip		Resistance	
	I_H , A	I_T , A	V_{MAX} , V _{DC}	I_{MAX} , A	P_d , W	Current	Time	R_{MIN}	$R1_{MAX}$
	A	Sec.	Ohm	Ohm					
FSMD075-0805RZ	0.75	1.50	6	100	0.6	8.0	0.20	0.040	0.160
FSMD110-0805RZ	1.10	1.80	6	100	0.6	8.0	0.30	0.030	0.130
FSMD125-0805RZ	1.25	2.50	6	100	0.6	8.0	0.30	0.025	0.110
FSMD150-0805RZ	1.50	3.00	6	100	0.6	8.0	0.30	0.015	0.065
FSMD175-0805RZ	1.75	3.50	6	100	0.6	8.0	0.60	0.005	0.055
FSMD200-0805RZ	2.00	4.00	6	100	0.6	8.0	1.00	0.005	0.045
FSMD300-0805RZ	3.00	6.00	6	100	0.6	8.0	5.00	0.003	0.030
FSMD350-0805RZ	3.50	7.00	6	100	0.6	8.0	5.00	0.002	0.025

I_H =Hold current-maximum current at which the device will not trip at 23°C still air.

I_T =Trip current-minimum current at which the device will always trip at 23°C still air.

V_{MAX} =Maximum voltage device can withstand without damage at it rated current (I_{MAX}).

I_{MAX} = Maximum fault current device can withstand without damage at rated voltage (V_{MAX}).

P_d =Typical power dissipated-type amount of power dissipated by the device when in the tripped state in 23°C still air environment.


R_{MIN} =Minimum device resistance at 23°C prior to tripping.

$R1_{MAX}$ =Maximum device resistance at 23°C measured 1 hour after tripping or reflow soldering of 260°C for 20 seconds.

Termination pad characteristics


Termination pad materials: Pure Tin

4. FSMD Product Dimensions (Millimeters)




Part Number	A		B		C		D		E	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
FSMD075-0805RZ	2.00	2.20	1.20	1.50	0.30	0.70	0.20	0.60	0.10	0.45
FSMD110-0805RZ	2.00	2.20	1.20	1.50	0.30	0.70	0.20	0.60	0.10	0.45
FSMD125-0805RZ	2.00	2.20	1.20	1.50	0.30	0.70	0.20	0.60	0.10	0.45
FSMD150-0805RZ	2.00	2.20	1.20	1.50	0.30	0.70	0.20	0.60	0.10	0.45
FSMD175-0805RZ	2.00	2.20	1.20	1.50	0.30	0.70	0.20	0.60	0.10	0.45
FSMD200-0805RZ	2.00	2.20	1.20	1.50	0.30	1.00	0.20	0.60	0.10	0.45
FSMD300-0805RZ	2.00	2.20	1.20	1.50	0.60	1.40	0.20	0.60	0.10	0.45
FSMD350-0805RZ	2.00	2.20	1.20	1.50	0.60	1.40	0.20	0.60	0.10	0.45

5. Thermal Derating Curve



6. Typical Time-to-Trip at 23°C

- A = FSMD075-0805RZ
- B = FSMD110-0805RZ
- C = FSMD125-0805RZ
- D = FSMD150-0805RZ
- E = FSMD175-0805RZ
- F = FSMD200-0805RZ
- G = FSMD300-0805RZ
- H = FSMD350-0805RZ




7. Material Specification

Terminal pad material: Pure Tin


Soldering characteristics: Meets EIA specification RS 186-9E, ANSI/J-std-002 Category 3

8. Part Numbering and Marking System

Part Numbering System



Part Marking System



- F = FSMD075-0805RZ
- H = FSMD110-0805RZ
- I = FSMD125-0805RZ
- J = FSMD150-0805RZ
- K = FSMD175-0805RZ
- M = FSMD200-0805RZ
- S = FSMD300-0805RZ
- V = FSMD350-0805RZ


Warning: - Each product should be carefully evaluated and tested for their suitability of application.



- Operation beyond the specified maximum rating or improper use may result in damage and possible electrical arcing and/or flame.
- PPTC device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
- Avoid contact of PPTC device with chemical solvent, including some inert material such as silicone based oil, lubricant and etc. Prolonged contact will damage the device performance.
- Additional protection mechanism are strongly recommended to be used in conjunction with the PPTC device for protection against abnormal or failure conditions.
- Avoid use of PPTC device in a constrained space such as potting material, housing and containers where have limited space to accommodate device thermal expansion and/or contraction.
- Avoid PPTC devices being exposed to prolonged high temperature and/or high humidity storage environment such as 85°C and/or 85RH% which could diminish PPTC's performance.

9. Pad Layouts 、 Solder Reflow and Rework Recommendations

The dimension in the table below provide the recommended pad layout for each Low Rho FSMD0805 device



Pad dimensions (millimeters)

Device	A Nominal	B Nominal	C Nominal
All FSMD0805 Series	1.20	1.00	1.50

Solder reflow

※ Due to “Lead Free” nature, Temperature and Dwelling time for the soldering zone is higher than those for Regular. This may cause damage to other components.

1. Recommended max paste thickness is 0.25mm. (Nominal)
2. Devices can be cleaned using standard methods and aqueous solvent.
3. Rework use standard industry practices.
4. Storage Environment : < 30°C / 60%RH.

Caution:

1. If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.
2. Devices are not designed to be wave soldered to the bottom side of the board.

Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate (T_{smax} to T_p)	3°C/second max.
Preheat:	
Temperature Min (T _{smin})	150°C
Temperature Max (T _{smax})	200°C
Time (t _{smin} to t _{smax})	60-180 seconds
Time maintained above:	
Temperature (T _L)	217°C
Time (t _L)	60-150 seconds
Peak/Classification Temperature (T_p) :	260°C
Time within 5°C of actual Peak :	
Temperature (t _p)	20-40 seconds
Ramp-Down Rate:	6°C/second max.
Time 25°C to Peak Temperature:	8 minutes max.

Note 1: All temperatures refer to of the package, measured on the package body surface.

Reflow Profile

