


### INTRODUCTION

The RMT series are thin film resistors. They feature a lower temperature coefficient than standard thick film types and are ideal for use in applications where temperature stability is important. These resistors are lead free.

### CONSTRUCTION




① Alumina Substrate	④ Bottom Inner Electrode	⑦ Side Inner Electrode
② Resistive Layer	⑤ Protective Overcoat	⑧ Nickel Barrier
③ Top Inner Electrode	⑥ Marking	⑨ Solder coating (Sn)

### FEATURES

- Tolerance to  $\pm 0.1\%$
- Low TCR to  $\pm 10 \text{ ppm}/^\circ\text{C}$
- Halogen free and lead free
- See RMTUH12 for Triple Power
- All Suffix Q for AECQ200 Type

### DIMENSIONS




Size Code	Max. Dimension (mm)				
	L	W	H	C	D
RMT02 (0201)	0.60 $\pm$ 0.05	0.30 $\pm$ 0.05	0.23 $\pm$ 0.05	0.15 $\pm$ 0.05	0.12 $\pm$ 0.05
RMT04 (0402)	1.00 $\pm$ 0.20	0.50 $\pm$ 0.15	0.30 $\pm$ 0.05	0.20 $\pm$ 0.10	0.20 $\pm$ 0.10
RMT06 (0603)	1.60 $\pm$ 0.20	0.80 $\pm$ 0.15	0.40 $\pm$ 0.10	0.30 $\pm$ 0.20	0.30 $\pm$ 0.15
RMT10 (0805)	2.00 $\pm$ 0.20	1.25 $\pm$ 0.20	0.50 $\pm$ 0.15	0.35 $\pm$ 0.15	0.35 $\pm$ 0.15
RMT12 (1206)	3.20 $\pm$ 0.20	1.60 $\pm$ 0.20	0.55 $\pm$ 0.15	0.45 $\pm$ 0.20	0.45 $\pm$ 0.20
RMT25 (1210)	3.20 $\pm$ 0.20	2.50 $\pm$ 0.20	0.55 $\pm$ 0.15	0.50 $\pm$ 0.20	0.50 $\pm$ 0.20
RMT50 (2010)	5.00 $\pm$ 0.20	2.50 $\pm$ 0.20	0.55 $\pm$ 0.10	0.60 $\pm$ 0.20	0.60 $\pm$ 0.20
RMT75 (2512)	6.30 $\pm$ 0.20	3.20 $\pm$ 0.20	0.55 $\pm$ 0.10	0.60 $\pm$ 0.20	0.60 $\pm$ 0.20

### RATINGS & RESISTANCE RANGE

Type	Rated Power at 70°C	Max. Working Voltage	Max. Overload Voltage	T.C.R. (PPM/C)	Resistance Range			
					B( $\pm 0.1\%$ )	C( $\pm 0.1\%$ )	D( $\pm 0.5\%$ )	F( $\pm 1\%$ )
RMT02 (0201)	0.05W	25V	50V	$\pm 10$ & $\pm 15$	10 $\Omega$ - 5.1K $\Omega$			
				$\pm 25$ & $\pm 50$	10 $\Omega$ - 82K $\Omega$			
RMT04 (0402)	0.063W	25V	50V	$\pm 10$ & $\pm 15$	10 $\Omega$ - 68K $\Omega$			
				$\pm 25$ & $\pm 50$	4.7 $\Omega$ - 220K $\Omega$	2.49 $\Omega$ - 220K $\Omega$		
RMT06 (0603)	0.1W	75V	150V	$\pm 10$ & $\pm 15$	10 $\Omega$ - 332K $\Omega$			
				$\pm 25$ & $\pm 50$	4.7 $\Omega$ - 680K $\Omega$	2.49 $\Omega$ - 680K $\Omega$		
RMT10 (0805)	0.125W	200V	300V	$\pm 10$ & $\pm 15$	10 $\Omega$ - 680K $\Omega$			
				$\pm 25$ & $\pm 50$	4.7 $\Omega$ - 1M $\Omega$	2.49 $\Omega$ - 1.0M $\Omega$		
RMT12 (1206)	0.25W	200V	400V	$\pm 10$ & $\pm 15$	10 $\Omega$ - 1M			
				$\pm 25$ & $\pm 50$	4.7 $\Omega$ - 1.5M $\Omega$	2.49 $\Omega$ - 1.5K $\Omega$		
RMT25 (1210)	0.25W			$\pm 10$ & $\pm 15$	10 $\Omega$ - 100K $\Omega$			
				$\pm 25$ & $\pm 50$	4.7 $\Omega$ - 100K $\Omega$	2.49 $\Omega$ - 100K $\Omega$		
RMT50 (2010)	0.5W			$\pm 10$ & $\pm 15$	10 $\Omega$ - 100K $\Omega$			
				$\pm 25$ & $\pm 50$	4.7 $\Omega$ - 100K $\Omega$	2.49 $\Omega$ - 100K $\Omega$		
RMT75 (2512)	0.75W	$\pm 10$ & $\pm 15$	10 $\Omega$ - 100K $\Omega$					
		$\pm 25$ & $\pm 50$	4.7 $\Omega$ - 100K $\Omega$	2.49 $\Omega$ - 100K $\Omega$				

### PART NUMBER EXAMPLE



### RESISTANCE CODE


Ohms	10	100	1.5K	15K	1M
Code	10R0	100R	1K50	15K0	1M00

### TOLERANCE CODE

Tolerance	$\pm 0.1\%$	$\pm 0.25\%$	$\pm 0.5\%$	$\pm 1\%$
Code	B	C	D	F

■ **PERFORMANCE CHARACTERISTICS**

■ **POWER DERATING CURVE**



Power rating or current rating is in the case based on continuous full-load at ambient temperature of 70°C. For operation at ambient temperature in excess of 70°C, the load should be derated in accordance with figure of derating Curve.

■ **VOLTAGE RATING OR CURRENT RATING**

Resistance Range:  $\geq 1\Omega$

Rated Voltage: The resistor shall have a DC continuous working voltage or a RMS AC continuous working voltage at commercial-line frequency and wave form corresponding to the power rating, as determined formula as follows:

$$E = \sqrt{P \times R}$$

E = Rated Voltage (V)


P = Power Rating (W)

R = Nominal Resistance ( $\Omega$ )


■ **OPERATION AND STORAGE TEMPERATURE**

TYPE	MIN	MAX
Operation temperature	-55°C	70°C
Storage temperature	20°C	30°C
Storage humidity	30%	70°C

■ **SOLDERING PROFILE**




### ■ TEST PROCEDURES & REQUIREMENTS

Test Item	Test Method	Procedure	Requirements
Temperature Coefficient of Resistance (T.C.R.)	JIS C 5201-1 Clause 4.8	-55°C ~ +155°C, 20°C is the reference temperature	Refer to Ratings
Short Time Overload	JIS C 5201-1 Clause 4.13	General: 2.5 times RCWV or Max. Overload voltage for 5 seconds High Power: 2.5 times RCWV or Max. Overload voltage for 2 seconds	±1: ±(1.0%+0.05Ω) ±5: ±(2.0%+0.1Ω)
IR Reflow	Sony SS-00254	 <p>The graph shows a temperature profile for IR reflow. The y-axis is temperature in °C (50 to 250) and the x-axis is heating time. Key points include: a pre-heating zone at 180°C, a dwell at 150°C for 90 ± 30 s, a peak at 250 ± 5 °C (230°C or higher), and a soldering zone at 30 ± 10 s.</p>	±1: ±(1.0%+0.05Ω) ±5: ±(2.0%+0.1Ω)
Leaching	Sony SS-00254-9	260 ±5°C for 30 seconds	> 95% Coverage
Soldering Heat	JIS C 5201-1 Clause 4.18	260 ±5°C for 10 seconds	±1: ±(0.5%+0.05Ω) ±5: ±(1.0%+0.05Ω)
Temperature Cycling	JIS C 5201-1 Clause 4.19	-55°C ~ +155°C, 5 cycles	0.1% ' 0.5% ' 1% ±(0.5%+0.05Ω) 2% ' 5% ±(1.0%+0.1Ω)
Electric Iron	Sony SS-00254-5	Preheating temperature: 350 ± 5°C Electric Iron preheating time: 3 +1/-0 sec.	±1: ±(0.5%+0.05Ω) ±5: ±(1.0%+0.05Ω)
Resistance to Solvent	JIS C 5201-1 Clause 4.29	The tested resistor be immersed into isopropyl alcohol of 20~25°C for 60 seconds. Then the resistor is left in the room for 48 hours.	±1: ±(0.5%+0.05Ω) ±5: ±(1.0%+0.05Ω)
Load Life in Humidity	JIS C 5201-1 Clause 4.24	40 ± 2°C, 90~95% R.H. or Max. working voltage for 1000 hours with 1.5 hrs "ON" and 0.5hr "OFF".	0.1% ' 0.5% ' 1% ±(0.5%+0.05Ω) 2% ' 5% ±(3.0%+0.1Ω)
Load Life (Endurance)	JIS C 5201-1 Clause 4.25	70 ± 2°C, or Max. working voltage for 1000 hours with 1.5 hrs "ON" and 0.5hr "OFF".	0.1% ' 0.5% ' 1% ±(1.0%+0.05Ω) 2% ' 5% ±(3.0%+0.1Ω)
Terminal Bending Strength	JIS C 5201-1 Clause 4.33	<b>Bend once for 5 seconds</b> RM Series 0402, 0603, 0805 = 5mm RM Series 1206, 1210, 1812 = 3mm RM Series 1218, 2010, 2512 = 2mm	±1: ±(1.0%+0.05Ω) ±5: ±(1.0%+0.05Ω)
Insulation Resistance	JIS C 5201-1 Clause 4.6	Max Overload Voltage for 1 min.	≥ 10G

■ **PACKAGE & DIMENSION**


Unit:mm



Size	Package Q'ty	A	B	C	D	W	M
RMT02(0201) RMT04(0402)	7" 10K/reel	2.0±0.5	13.5±1.0	21±1.0	60±1.0	11.5±2.0	178±2.0
RMT06(0603) RMT10(0805) RMT12(1206)	7" 5K/reel 10" 10K/reel 13" 20K/reel	2.0±0.5	13.5±1.0	21±1.0	60±1.0 100±1.0 100±1.0	11.5±2.0	178±2.0 254±2.0 330±2.0
RMT25(1210) RMT50(2010) RMT75(2512)	7" 5K/reel 7" 4K/reel	2.0±0.5	13.5±1.0	21±1.0	60±1.0	11.5±2.0 16.0±2.0	178±2.0

■ **TAPING SPECIFICATION**


Paper Type  
(P= 2.0 ± 0.1)



Unit:mm

Size	A	B	W	E	F	G	H	T	D
RMT02(0201)	0.45±0.10	0.75±0.10	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.35±0.10	1.50±0.10
RMT04(0402)	0.70±0.10	1.20±0.10	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.45±0.10	1.50±0.10
RMT06(0603)	1.05±0.20	1.80±0.20	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.60±0.10	1.50±0.10
RMT10(0805)	1.55±0.20	2.30±0.20	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.75±0.10	1.50±0.10
RMT12(1206)	1.90±0.20	3.50±0.20	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.75±0.10	1.50±0.10
RMT25(1210)	2.85±0.20	3.50±0.20	8.0±0.20	1.75±0.10	3.5±0.05	4.0±0.10	2.0±0.05	0.75±0.10	1.50±0.10

Embossed Type  
(P= 4.0 ± 0.1)  
(2W.P= 8.0 ± 0.2)



Unit:mm

Size	A	B	W	E	F	G	H	T	D	D1	T1
RMT50(2010)	2.80±0.20	5.60±0.20	12±0.10	1.75±0.10	5.5±0.05	4.0±0.10	2.0±0.05	0.23±0.10	1.50±0.10	1.50±0.10	0.85±0.15
RMT75(2512)	3.30±0.20	4.60±0.20	12±0.10	1.75±0.10	5.5±0.05	4.0±0.10	2.0±0.05	0.23±0.10	1.50±0.10	1.50±0.10	0.85±0.15